

# Specifications

## LSP Duct (drain pump included)

- High efficiency microchannel heat exchanger.
- Built-in electronic expansion valve (EEV) for refrigerant flow control (2000-step).
- Auto Restart function.
- Condensation drain pump.
- Long-life HD 40 permanent filter is included.
- Auto ESP function.
- SPI Ioniser.



Indoor Unit			AJ026TNLDEG/EU	AJ035TNLDEG/EU
<b>Capacity</b>				
	Cooling	kW	2.6	3.5
	Heating up to +7 °C	kW	2.9	3.8
<b>Performance</b>				
Airflow Rate		m <sup>3</sup> /min	8.6/7.6/6.6	9.8/8.8/7.8
Sound Power	Cooling	dB(A)	53	53
Sound Pressure	H/M/L	dB(A)	30/28/25	32/30/27
<b>Electrical Data</b>				
Power Source		Φ, #, V, Hz	1Φ, 2, 220-240 V, 50 Hz	1Φ, 2, 220-240 V, 50 Hz
Power Consumption	Cooling	W	80	80
	Heating	W	80	80
Current Input	Cooling	A	0.4	0.4
	Heating	A	0.4	0.4
<b>Dimensions</b>				
Net Dimensions (W x H x D)		mm	900 x 199 x 600	900 x 199 x 600
Net Weight		kg	23.3	23.3
<b>Refrigerant</b>				
Piping Connections	Liquid Pipe	ø, inch	1/4	1/4
	Gas Pipe	ø, inch	3/8	3/8
Piping Connections	Drain Pipe	ø, mm	VP25 (OD 32, ID 25)	VP25 (OD 32, ID 25)
<b>Others</b>				
Accessories	Drain Pump		MDP-E075SEE3	MDP-E075SEE3
	Max. Lifting Height/ Displacement	mm / litres/h	750/24	750/24
	Air Filter		Removable/Washable	Removable/Washable

### Accessories



Advanced Wired Controller	Simple Type Controller	Touch Controller	Wired Remote Controller	Wi-Fi Kit
MWR-WG00JN/MWR-WG00KN	MWR-SH00N	MWR-SH11N	MWR-WE13N	MIM-H04EN